

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-096614

(43)Date of publication of application : 02.04.2002

(51)Int. CI.

B60C 17/04

B60C 5/08

(21)Application number : 2000-292254 (71)Applicant : BRIDGESTONE CORP


(22)Date of filing : 26.09.2000 (72)Inventor : TAKATSUKI TETSUYA

(54) SAFETY PNEUMATIC TIRE

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a safety pneumatic tire, simply structured, allowing easy manufacturing and rim assembling with low material cost, and excellent in fuel saving performance and safety.

SOLUTION: A hollow toroidal core 2 reinforced by a reinforcing layer 2b comprising spiral cords so as to have a ratio of the diametral increase of less than 10% is disposed inside a tubeless tire 1, keeping the inflation pressure of the core 2 nearly at the same level as that of the tubeless tire 1 while the ratio h/H of the core height h under the pressure to the maximum height H of the inner circumferential surface inside the tread part at $1/3 \leq h/H \leq 4/5$.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office